



## FEATURE SPECIFICATIONS

### Basic Features

#### Business Features:

- » Flexible time-based call routing
- » Built in conference bridge/service
- » Fax to email
- » Hunt / Ring groups
- » Music on hold
- » Voicemail blasting
- » Follow me / Find me calling
- » Personal IVRs
- » Wake up calls
- » Support for video calls, IM & presence
- » Secure communications (SRTP/ TLS)
- » Directory & Dictation
- » Calling queues (ACD/IVR)
- » Customizable announcements

#### Calling Features:

- » Three way calling
- » Voicemail
  - » Voicemail to email
- » Caller ID
- » Call transfer
- » Call recording
- » Do not disturb
- » Call forwarding
- » Call waiting
- » Call history
  - » Call detail records and call event logging
- » Speed dials
- » Caller blacklisting
- » Paging / Intercom
- » Call screening
- » DISA

#### Telephony Support:

- » Open standards support for multiple signaling protocols
  - » SIP
  - » IAX2
  - » PRI/T1/E1
  - » POTS/Analog
  - » ISDN
- » Soft phone support
- » WebRTC
  - » Browser-based calling (thru UCP)
- » Specialty device support
  - » Door phones
  - » Overhead paging
  - » Strobe alerts
  - » Paging & voice gateways
  - » Failover devices

#### Multiple Language Support:

- » English
- » Bulgarian
- » Chinese
- » German
- » Hebrew
- » Hungarian
- » Italian
- » Portuguese
- » Russian
- » Swedish
- » Spanish
- » Japanese

#### End User Applications:

- » User Control Panel (UCP)

### Administration:

- » Bulk import utilities
  - » Trunks
  - » Extensions
  - » Users
  - » Phone numbers
- » System dashboards
- » Integrated intrusion detection

### Physical Features

#### FreePBX 10:

- » Shipping dimensions
  - » 127mm (W) x 127mm (D) x 19mm (H)
- » Shipping weight
  - » .91kgs (2lbs)
- » External universal AC/DC power brick
- » Single 32GB SSD drive

#### FreePBX 60:

- » Shipping dimensions
  - » 324mm (W) x 267mm (D) x 70mm (H)
- » Shipping weight
  - » 9.1kgs (20lbs)
- » Internal 100~240V power supply
- » Single 120GB SSD drive

#### FreePBX 100:

- » Shipping dimensions
  - » 324mm (W) x 267mm (D) x 70mm (H)
- » Shipping weight
  - » 9.1kgs (20lbs)
- » Internal 100~240V power supply
- » Single 250GB SSD drive

#### FreePBX 300:

- » Shipping dimensions
  - » 432mm (W) x 317mm (D) x 44.5mm (H)
- » Shipping weight
  - » 9.1kgs (20lbs)
- » Internal 100~240V power supply
- » Dual 120GB SSD raid drives

#### FreePBX 1000:

- » Shipping dimensions
  - » 508mm (W) x 432mm (D) x 45mm (H)
- » Shipping weight
  - » 17.2kgs (38lbs)
- » Dual modular internal 100~240V power supplies
- » Dual 512GB SSD raid drives

#### FreePBX 5000:

- » Shipping dimensions
  - » 610mm (W) x 851mm (D) x 273mm (H)
- » Shipping weight
  - » 27.2kgs (60lbs)
- » Dual modular internal 100~240V power supplies
- » Quad 512GB SSD raid drives

### Enhanced Features

#### Licensing Options:

- » XactView
  - » Call management and presence desktop for end users
- » Zulu UC (20 Pack)
  - » Desktop integration
- » Call/Contact Center Features
  - » Enhanced call center functionality
- » EndPoint Manager
  - » Third party phone support for non-Sangoma IP phones
- » High Availability
  - » 1:1 active/standby two-box redundancy to guarantee business continuity